

DISK - HARROW Model 10 x 28

10 ft Wide

28" Disk



Overall Width: 9'-0"
 Overall Length: 23'-6"
 Total Weight: 7600 lbs.

Weight per Blade: 475 lbs.
 Gang Angle: 36 degrees (18 front, 18 rear)
 Recommended HP: 150

SPECIFICATIONS:

<p>MAIN FRAME</p> <p>6"x 6"x 3/8" wall square tubing 100 % welded Gussets 4"x12" rectangular tubing provides rigid support</p> <p>GANGS</p> <p>28"x1/2" serrated blades Greaseable cone bearings Blade spacing: 14" 2 1/8" diameter axle Blade scrapers: 3/8" hardox plate Angled for maximum cleaning</p> <p>GANG MOUNTS</p> <p>4"x6"x1/2" wall rectangular tubing 1" steel mounting plates, 1" bolts</p> <p>AXLE ASSEMBLY</p> <p>6"x6"x3/8" wall square tubing 10,000 lb. Spindles, 10 bolt hubs Oil bath bearings 385 65R 22.5 tires - Optional foam filled tires adds 900 lbs. to total weight</p> <p>HYDRAULIC COUPLERS</p> <p>Standard Pioneer ends</p>	<p>CENTER LIFT CYLINDER</p> <p>Trunnion mounted 24" stroke, 2 1/2" rod Spherical ball bearing end</p> <p>HITCH</p> <p>Fully rotatable & field replaceable Accommodates 1 1/2" pin Greaseable bushing Category 4 4 1/2" minimum clevis opening req'd.</p> <p>TONGUE</p> <p>Hydraulically adjustable 6"x6"x1/2" wall square tubing Gusseted 1/2" plate</p> <p>TONGUE HINGE POINTS</p> <p>1"x6" steel, 1/4" end caps</p> <p>TONGUE PIVOT POINTS</p> <p>2 ea. 2"x10" hardened shafts Greaseable</p> <p>TONGUE CYLINDER</p> <p>12" stroke 2 1/2" rod 5" barrel 3,000 psi</p> <p>COLOR</p> <p>Custom colors available Std: Frame is white, Blades are black</p>
---	---

E-ject Systems
 1003 Miller Street
 Elkader, Iowa 52043

Phone (563) 245-1445
 Fax (563) 245-1440
www.ejectsystems.com