

# HEAVY DUTY SCARIFIER for D-4 or D-5



## DESIGN FEATURES

12" GROUND PENETRATION

HEAVY DUTY GREASED PIVOT POINTS

UTILIZES ENTIRE WIDTH OF TRACTOR

SHANKS ARE 1 1/2" THICK & TIPPED WITH  
HIGH ABRASIVE RESISTANT STEEL PLATES  
& THEN FACED WITH HARD SURFACED WELD

2 CYLINDERS FOR MAXIMUM POWER

MOUNTING BRACKETS BOLT UP TO  
EXISTING HOLES IN TRACTOR

RUGGED FRAME DESIGN USES  
6"x6"x1/2" THICK TUBING

## SPECIFICATIONS

GROUND PENETRATION = 12"

CYLINDER: 4" BORE, 16" STROKE, 3000 psi

GROUND CLEARANCE = 13"

INDUSTRIAL HYD. HOSE & ENDS 3500 psi

WIDTH = 109"

CYLINDER PINS 1 1/2" DIA.

7 SHANKS

HOOK-UP PINS 2 1/2" DIA.

### **E-ject Systems**

1003 Miller Street  
Elkader, Iowa 52043

Phone (563) 245-1445  
Fax (563) 245-1440  
[www.ejectsystems.com](http://www.ejectsystems.com)